

D-Cup 78 XTM



Product Data Sheet:

Description: Double braid rope.

Commercial name: D-Cup 78 XTM

Specifications:

Core: 12 strands, PU coated.		Cover : 24 plait / 32 plait	
Material:	Dyneema Sk 78 ®	Material:	Polyester®
Specific Gravity-	HMPE- 0.98	Specific Gravity-	Polyester - 1.38
UV Ranking - HMPE	Dyneema® - 5	UV Ranking -	Polyester – 5
Melting Point (Degrees C)	HMPE – 150	Melting Point (Degrees C)	Polyester- 260

Breaking Load:

Diameter		Weight			Breaking Load		
mm	inches	ktex	Kg/100m	lbs/100ft	kgf	lbf	kN
6	1/4	27	2,7	1,8	2 553	5 628	25,0
7	9/32	38	3,8	2,6	3 850	8 488	37,8
8	5/16	55	5,5	3,7	4 200	9 259	41,2
9	3/8	59	5,9	4,0	5 800	12 787	56,9
10	13/16	73	7,3	4,9	6 800	14 991	66,7
11	7/16	85	8,5	5,7	7600	16 755	74,5
12	1/2	114	11,4	7,7	8 580	18 915	84,1
Elongation at 10% of BL					0,31%		
Elongation at 20% of BL					0,53%		
Elongation at 30% of BL					0,73%		
Elongation at 40% of BL					0,92%		
Elongation at 50% of BL					1,14%		

* In accordance with the ISO 10325 2018