

Top Cruiser MAX Kmix Tn



Product Data Sheet:

Description: Double braid rope.

Commercial name: Top Cruiser MAX Kmix Technora

Specifications:

Core: 12 strands, PU coated.			Cover : 24 plait / 32 plait		
Material: Blend	Dyneema Sk 78 [®]	PP Multi	Material: Blend	Polyester [®]	Technora [®]
Specific Gravity-	HMPE- 0.98	0,91	Specific Gravity-	Polyester - 1.38	Aramid-1.44
UV Ranking	Dyneema - 5	PP Multi-2	UV Ranking -	Polyester – 5	Aramid- 3
Melting Point (Degrees C)	150	170	Melting Point (Degrees C)	Polyester- 260	500 (decomp.)

Breaking Load:

Diameter		Weight			Breaking Load			Av. Elongation	
mm	inches	ktex	Kg/100m	lbs/100ft	kgf	lbf	kN	50%BL	Total
8	5/8	42,7	4,2	2,8	2 600	5 732	25,5	1,6	3,2
10	13/16	68,0	6,8	4,6	4 300	9 480	42,2	1,6	3,2
12	1/2	95,4	9,5	6,4	5 000	11 023	49,0	1,6	3,2
14	9/16	124	12,4	8,3	7 600	16 755	74,5	1,6	3,2

* In accordance to ISO 10325:2018