

## Top Cruiser MAX Kmix



### Product Data Sheet:

Description: Double braid rope.

Commercial name: Top Cruiser MAX Kmix

Specifications:

Core: 12 strands, PU coated.			Cover : 24 plait / 32 plait		
Material: Blend	Dyneema Sk 78 <sup>®</sup>	PP Multi	Material: Blend	Polyester <sup>®</sup>	Cordura <sup>®</sup>
Specific Gravity-	HMPE- 0.98	0,91	Specific Gravity-	Polyester - 1.38	Nylon-1,14
UV Ranking	Dyneema - 5	PP Multi-2	UV Ranking -	Polyester – 5	Nylon-4
Melting Point (Degrees C)	150	170	Melting Point (Degrees C)	Polyester- 260	150

Breaking Load:

Diameter		Weight			Breaking Load			Av. Elongation	
mm	inches	ktex	Kg/100m	lbs/100ft	kgf	lbf	kN	50%BL	Total
6	1/2	27	2,7	1,8	1.524	3.360	14,9	1,6	3,2
7	9/16	29,3	2,9	2,0	2.000	4.409	19,6	1,6	3,2
8	5/8	37,5	3,8	2,5	2.564	5.653	25,1	1,6	3,2
10	13/16	58	5,8	3,9	4.040	8.907	39,6	1,6	3,2
11	7/16"	78,85	7,885	5,3	4.293	9464	42,1	1,6	3,2
12	1/2	82,2	8,2	5,5	4.880	10.758	47,9	1,6	3,2

\* In accordance to ISO 10325:2018