

Top Cruiser MAX Kmix



Product Data Sheet:

Description: Double braid rope.

Commercial name: Top Cruiser MAX Kmix

Specifications:

Core: 12 strands, PU coated.			Cover : 24 plait / 32 plait		
Material: Blend	Dyneema Sk 78 [®]	PP Multi	Material: Blend	Polyester [®]	Cordura [®]
Specific Gravity-	HMPE- 0.98	0,91	Specific Gravity-	Polyester - 1.38	Nylon-1,14
UV Ranking	Dyneema - 5	PP Multi-2	UV Ranking -	Polyester – 5	Nylon-4
Melting Point (Degrees C)	150	170	Melting Point (Degrees C)	Polyester- 260	150

Breaking Load:

Diameter		Weight			Breaking Load		
mm	inches	ktex	Kg/100m	lbs/100ft	kgf	lbf	kN
6	1/2	27	2,7	1,8	1.524	3.360	14,9
7	9/16	29,3	2,9	2,0	2.000	4.409	19,6
8	5/8	37,5	3,8	2,5	2.564	5.653	25,1
10	13/16	58	5,8	3,9	4.040	8.907	39,6
11	7/16"	78,85	7,885	5,3	4.293	9464	42,1
12	1/2	82,2	8,2	5,5	4.880	10.758	47,9
14	9/16	136,7	13,7	9,2	7.600	16.755	74,5
16	5/8	155,1	15,5	10,4	11.180	24.647	109,6
18	3/4	194	19,4	13,0	12.800	28.219	125,5

* In accordance with the ISSO 10325 2009