

Top Cruiser MAX Kmix



Product Data Sheet:

Description: Double braid rope.

Commercial name: Top Cruiser MAX Kmix

Specifications:

Core: 12 strands, PU coated.			Cover : 24 plait / 32 plait		
Material: Blend	Dyneema Sk 78 [®]	PP Multi	Material: Blend	Polyester [®]	Cordura [®]
Specific Gravity-	HMPE- 0.98	0,91	Specific Gravity-	Polyester - 1.38	Nylon-1,14
UV Ranking	Dyneema - 5	PP Multi-2	UV Ranking -	Polyester – 5	Nylon-4
Melting Point (Degrees C)	150	170	Melting Point (Degrees C)	Polyester- 260	150

Breaking Load:

Diameter		Weight			Breaking Load		
mm	inches	ktex	Kg/100m	lbs/100ft	kgf	lbf	kN
6	1/4	27,6	2,76	1,85	1 524	3 360	14,9
7	9/16	33,3	3,33	2,24	1 767	3 896	17,3
8	5/16	47,3	4,73	3,18	2 564	5 653	25,1
9	3/8	54,3	5,43	3,65	2 730	6 019	26,8
10	13/16	67,8	6,78	4,56	4 316	9 515	42,3
Elongation at 10% of BL					0,50%		
Elongation at 20% of BL					0,80%		
Elongation at 30% of BL					1,00%		
Elongation at 40% of BL					1,20%		
Elongation at 50% of BL					1,50%		

* In accordance with the ISO 10325 2018